

ISSN : 2301-6590



# Proceedings ICETD 2012

The First International Conference in  
Engineering and Technology Development



**Universitas Bandar Lampung**  
**20 - 21, June 2012**  
**Lampung, Indonesia**



## PREFACE

The activities of the International Conference is in line and very appropriate with the vision and mission of the UBL to promote training and education as well as research in these areas.

On behalf of the First International Conference of Engineering and Technology Development (ICETD 2012) organizing committee; we are very pleased with the very good responses especially from the keynote speakers and from the participants. It is noteworthy to point out that about 45 technical papers were received for this conference

The participants of conference come from many well known universities, among others: Universitas Bandar Lampung, International Islamic University Malaysia, University Malaysia Trengganu, Nanyang Technological University, Curtin University of Technology Australia, University Putra Malaysia, Jamal Mohamed College India, ITB, Mercu Buana University, National University Malaysia, Surya Institute Jakarta, Diponegoro University, Unila, Universitas Malahayati, University Pelita Harapan, STIMIK Kristen Newmann, BPPT Lampung, Nurtanio University Bandung, STIMIK Tarakanita, University Sultan Ageng Tirtayasa, and Pelita Bangsa.

I would like to express my deepest gratitude to the International Advisory Board members, sponsors and also welcome to all keynote speakers and all participants. I am also grateful to all organizing committee and all of the reviewers which contribute to the high standard of the conference. Also I would like to express my deepest gratitude to the Rector which give us endless support to these activities, such that the conference can be administrated on time.

Bandar Lampung, 20 Juni 2012

**Mustofa Usman, Ph.D**  
**ICETD Chairman**

**PROCEEDINGS**  
**The First International Conference in**  
**Engineering and Technology Development**  
**(ICETD 2012)**

**UNIVERSITAS BANDAR LAMPUNG**  
Bandar Lampung, Indonesia  
June, 20-21 2012

**Sterring Commite**

**Chairman**

Mustofa Usman

**Co-Chairman**

Marzuki

**Technical Committee**

Ahmad Cucus

Agus Sukoco

Dina Ika Wahyuningsih

**Treasure**

Maria Shusanti Febrianti

**Committee Member**

Indyah Kumoro

Fritz Akhmad Nuzir

Baginda Simaimban

Berry Salatar

Harpain

Yuthsi Aprilinda

Usman Rizal

Andala Rama P. Barusman

Yanuar Dwi Prasetyo

**International Advisory Board**

Ahmad F. Ismail, Malaysia

Hon Wei Leong, Singapore

Mustofa Usman, Indonesia

Imad Khamis, USA

Moses L. Singih, Indonesia

Y. M. Barusman, Indonesia

Andreas Dress, Germany

Rozlan Alias, Malaysia

Faiz A.M. Elfaki, Malaysia

Rudi Irawan, Indonesia

Warsono, Indonesia

Gusri Ibrahim, Indonesia

Raihan Othman, Malaysia

Jamal I Daoud, Malaysia

Zeng Bing Zen, China

Riza Muhida, Indonesia

Tjin Swee Chuan, Singapore

Heri Riyanto, Indonesia

Khomsahrial R, Indonesia

Agus Wahyudi, Indonesia

Rony Purba, Indonesia

Lilies Widodojoko, Indonesia

Alex Tribuana S, Indonesia

## **Organizing Committee**

### **Chair Person**

Prof. DR. Khomsahrial Romli, M.Si

### **Vice Chair Person**

Drs. Harpain, M.A.T., M.M

### **Secretary**

Fritz Akhmad Nuzir, S.T., M.A  
Ahmad Cucus, S.Kom., M.Kom

### **Treasure**

Dian Agustina, S.E

### **Special Events**

DR. Zulfi Diane Zaini, SH., MH  
DR. Baginda Simaibang, M.Ed  
Zainab Ompu Jainah, SH., MH  
DR. Alex Tribuana S., ST., MM  
Erlangga, S.Kom

### **Recepcionist**

Berry Salatar, A.Md  
Yanuar Dwi Prasetyo, S.Pd.I., M.A  
Siti Rahma Wati, S.E  
Ardiansyah, ST., MT  
Sofie Islamia Ishar, S.T., M.T  
Taqwan Thamrin, S.T., M.Sc

### **Transportation and Acomodation**

Irawati, SE  
Usman Rizal, S.T., MMSi  
Hendri Dunan, S.E., M.M  
Rifandi Ritonga, S.H  
Desi Puspita Sari, S.E  
Roby Yuli Endra, S.Kom  
Tanto Lailam, S.H  
Ilyas Sadad, S.T., M.T

### **Publication and Documentation**

Ir. Indriati Agustina Gultom, M.M  
Monica Mutiara Tinambunan, S.I.Kom., M.I.Kom  
Noning Verawati, S.Sos  
Hesti, S.H  
Rifandi Ritonga, SH

Olivia Tjioener, S.E., M.M  
Violita, S.I.Kom

**Cosumption**

Dra. Yulfriwini, M.T  
Dra. Agustuti Handayani, M.M  
Susilowati, ST., MT  
Wiwin Susanty, S.Kom  
Reni Nursyanti, S.Kom  
DR.Dra. Ida Farida, M.Si

**Facility and Decoration**

Zainal Abidin, SE  
Ahyar Saleh, SE  
Eko Suhardiyanto  
Dina Ika Wahyuningsih, A.Md  
Wagino  
Sugimin

## **Table Of Content**

Organizing Committee.....	i
Table Of Content.....	v
<b>Keynote Speaker</b>	
1. Zinc-Air Battery – Powering Electric Vehicles to Smart Active Labels <b>Dr. Raihan Othman</b> .....	1
2. Enhancing Heat Transfer Using Nanofluids(abstract) <b>Prof. Ahmad Faris Ismail</b> .....	6
3. Rapid Prototyping and Evaluation for Green Manufacturing <b>RizaMuhida, Ph.D</b> .....	7
4. Indonesia’s Challenge to Combat Climate Change Using Clean Energy <b>Rudi Irawan, Ph.D</b> .....	12
5. Paraboloid-Ellipsoid Programming Problem <b>Prof.Dr. Ismail Bin Mohd</b> .....	15
6. Model Development of Children Under Mortality Rate With Group Method of Data Handling <b>Dr. IingLukman</b> .....	27
7. The Modified CW1 Algorithm For The Degree Restricted Minimum Spanning Tree Problem <b>Wamiliana, Ph.D</b> .....	36
8. The Fibre Optic Sensor in Biomedical Engineering and Biophotonics <b>Prof. TjinSweeChuan</b> .....	
<b>Speaker</b>	
1. Web-Based Service Optimization with JSON-RPC Platform in Java and PHP <b>WachyuHari Haji</b> .....	1
2. Trouble Ticketing System Based Standard ISO10002: 2004 To Improve Handling of Complaints Responsibility <b>Ahmad Cucus, Marzuki, AgusSukoco, Maria ShusantiFebrianti, Huda Budi Pamungkas</b> .....	6
3. Design of Warehouse Management Application Tool for Controlling The Supply Chain <b>Anita Ratnasari, Edi Kartawijaya</b> .....	10
4. Development Of Decision Related Engine Using Integration Of Genetic Algorithm And Text Mining <b>EvianaTjaturPutri, Mardalena, Asmah</b> .....	15
5. Implementing CBR on The College Rankings Based on Webometrics with EPSBED’s Data and Webometrics Knowledge	

	<b>Marzuki , Maria Shusanti F, Ahmad Cucus , AgusSukoco</b> .....	19
6.	Paypal Analysis as e-Payment in The e-Business Development <b>Nomi Br Sinulingga</b> .....	24
7.	Decision Support System for Determination of Employees Using Fuzzy Decision Tree <b>Sinawaty#1, YusniAmaliah</b> .....	28
8.	Analysis of Factors Influencing Consumer Behavior Bring Their Own Shopping Bag (Case Study KecamatanTembalang) <b>Aries Susanty, DyahIkaRinawati, FairuzZakiah</b> .....	33
9.	The Use of Edge Coloring Concept for Solving The Time Schedule Problem at Senior High School (Case Study at SMAN 9 Bandarlampung) <b>RahmanIndraKesuma, Wamiliana, MachudorYusman</b> .....	41
10.	Analysis Of Web-Education Based on ISO / IEC 9126-4 For The Measurement Of Quality Of Use <b>Marzuki, AgusSukoco, Ahmad Cucus, Maria ShusantiFebrianti, Lisa Devilia</b> .....	46
11.	The Used of Video Tracking for Developing a Simple Virtual Boxing <b>David HabsaraHareva, Martin</b> .....	55
12.	M-Government as Solutions for E-Government problems in Indonesia <b>Ahmad Cucus, Marzuki, AgusSukoco, Maria ShusantiFebrianti</b> .....	60
13.	Open Source ERP for SME <b>Tristiyanto</b> .....	65
14.	Improvement in Performance of WLAN 802.11e Using Genetic Fuzzy Admission Control <b>SetiyoBudyanto</b> .....	70
15.	Cloud Computing: Current and Future <b>TaqwanThamrin, Marzuki, Reni Nursyanti, Andala Rama Putra</b> .....	75
16.	Implementing Information Technology, Information System And Its Application In Making The Blue Print for The One Stop Permission Services <b>Sri AgustinaRumapea, HumuntalRumapea</b> .....	80
17.	Integration System Of Web Based And SMS Gateway For Information System Of Tracer Study <b>EndykNoviyantono, Aidil</b> .....	86
18.	Fuzzy Logic Applied To Intelligent Traffic Light <b>EndykNoviyantono, Muhammad</b> .....	93
19.	Solving and Modeling Ken-ken Puzzleby Using Hybrid Genetics Algorithm <b>Olivia Johanna, Samuel Lukas, Kie Van IvankySaputra</b> .....	98
20.	GIS Habitat Based Models Spatial Analysis to Determine The Suitability Of Habitat For Elephants <b>AgusSukoco</b> .....	103

21. The Course Management System Workflow-Oriented to Control Admission and Academic Process <b>Usman Rizal, YuthsiAprilinda</b> .....	108
22. Fuzzy Graphs With Equal Fuzzy Domination And Independent Domination Numbers <b>A.Nagoorgani, P. Vijayalakshmi</b> .....	115
23. Solving Pixel Puzzle Using Rule-Based Techniques and Best First Search <b>Dina Stefani, Arnold Aribowo, Kie Van IvankySaputra, Samuel Lukas</b> .....	118
24. Capacity Needs for Public Safety Communication Use 700 MHz as Common Frequencyin Greater Jakarta Area <b>SetiyoBudiyanto</b> .....	125
25. Impact of Implementation Information Technology on Accounting <b>Sarjito Surya</b> .....	132
26. Document Management System Based on Paperless <b>WiwinSusanty, TaqwanThamrin, Erlangga, Ahmad Cucus</b> .....	135
27. Traceability Part For Meter A14C5 In PT Mecoindo Of The Measurement Of Quality Of Use <b>Suratman, WahyuHadiKristanto, AsepSuprianto, MuhamadFatchan, DendyPramudito</b> .....	139
28. Designing and Planning Tourism Park with Environment and Quality Vision and Information Technology-Based(Case Study: Natural Tourism Park Raman Dam) <b>Fritz A. Nuzir, AgusSukoco, Alex T</b> .....	149
29. Smart House Development Based On Microcontroller AVR-ATMEGA328 <b>Haryansyah, Fitriansyah Ahmad, Hadriansa</b> .....	157
30. Analyze The Characteristic of Rainfall and Intensity Duration Frequency (IDF) Curve at Lampung Province <b>Susilowati</b> .....	161
31. The Research of Four Sugarcane Variety ( <i>Saccharum officinarum</i> ) as The Raw Materials of Bioethanol Production in Negara Bumi Ilir Lampung <b>M.C.Tri Atmodjo, Agus Eko T, Sigit Setiadi, Nurul Rusdi, Ngatinem JP, Rina, Melina, Agus Himawan</b> .....	174
32. Design an Inverter for Residential Wind Generator <b>Riza Muhida, Afzeri Tamsir, Rudi Irawan, Ahmad Firdaus A. Zaidi</b> .....	177
33. The Research of Two Sugarcane Variety ( <i>Saccharum officinarum</i> ) as The Raw Materials of Bioethanol Production in Negara Bumi Ilir - Lampung <b>M.C. Tri Atmodjo, Agus Eko T., Sigit Setiadi, Nurul Rusdi, Ngatinem JP, Rina, Melina, Agus H.</b> .....	182
34. Design of Plate Cutting Machine For Cane Cutter ( <i>Saccharum Oficinarum</i> ) Use Asetilin Gas <b>M,C, Tri Atmodjo, Tumpal O.R, Sigit D.Puspito</b> .....	186



35.	Behaviour of Sandwiched Concrete Beam under Flexural Loading <b>Firdaus, Rosidawani</b> .....	191
36.	Diesel Particulate Matter Distribution of DI Diesel Engine Using Tire Disposal Fuel <b>Agung Sudrajad</b> .....	196
37.	Microstructure Alterations of Ti-6Al-4V ELI during Turning by Using Tungsten Carbide Inserts under Dry Cutting Condition Ibrahim, G.A. Arinal, H, Zulhanif, Haron, C.H.C .....	200
38.	Validation Study of Simplified Soil Mechanics Method Design with Kentledge Pile Loading Test of Bored Pile Lilies Widodojoko .....	204
39.	Performance Assessment Tool for Transportation Infrastructure and Urban Development for Tourism Diana Lisa .....	211
40.	Earthquake Resistant House Building Structure Ardiansyah .....	221

# Validation Study of Simplified Soil Mechanics Method Design with Kentledge Pile Loading Test of Bored Pile

Lilies Widodojoko

University of Bandar Lampung, Jl Z.A.Pagar Alam no 26, Bandar Lampung, 35142, Indonesia

labtekniksipil\_lw@yahoo.co.id

**Abstract:** The use of static load testing in optimising design and providing verification of suitability and constructability continues to be unsurpassed in the foundation industry.

Another purpose of that load testing is either to validate the design before construction and/or to check compliance with the specification during construction. The aim of this paper is to validate the design by comparing the ultimate load of Kentledge bored pile loading test with the its design, using Simplified Soil Mechanics method. The difference between Kentledge loading test and Simplified Soil Mechanics method are 13 % and 25%, if the pile bearing ultimate capacity of Kentledge loading test is computed using Mazurkiewicz and Davisson MT method.

**Keywords :** Kentledge bored pile loading test , Simplified Soil Mechanics Method Bore Pile Design, Mazurkiewicz and Davisson MT method

## I. INTRODUCTION

Producing competent bored piles is one of the most difficult tasks facing a civil engineer. Since their production process is carried out in a hostile underground environment and is largely invisible, bored piles unavoidably contain flaws. On the otherhand, replacement of faulty foundation piles is at best impractical. This is the reason why quality control of finished foundation piles grew to rely on various methods. A flaw is any deviation from the planned shape and/or material of the pile (Amir, 2002). It may thus involve inclusions of foreign material, necking, bulging and also piles that are too short. Table 1 shows the flaw occurrence ratio. Pile load testing provides an opportunity for continuous improvement in foundation design and construction practices, while at the same time fulfilling its traditional role of design validation and routine quality control of the piling works.

The strategy for pile testing needs to be established at the time the piles are being designed. For most projects the main purpose of pile testing is either to validate the design before construction and/or to check compliance with the specification during construction. However in some cases there are benefits in using testing for design development or research to provide the best solution. Testing strategies can therefore be divided into four main categories: (1) Design validation, (2) Quality control, (3) Design development and (4) Research.

The scope of testing will depend on the complexity of the foundation solution, the nature of the site and the

consequences if piles do not meet the specified requirements. The pile designer therefore needs to assess the risks and develop the testing regime accordingly.

The main risks are: (1) Insufficient site investigation, (2) Lack of experience of similar piles in similar ground conditions, (3) Insufficient time to verify the pile design and realise any savings (4) Cost and programme implications of undertaking the pile tests, (5) Cost and programme implications of a foundation failure for simple structures on a site where the ground conditions are well understood and there is pile test data from adjacent sites that have used similar piling solutions, then the risks are low and pile load testing can usually be restricted to routine checks for compliance or can even be omitted.

For situations where the ground conditions or structural requirements are complex, or there is little experience of similar piling work, then careful evaluation of the piling proposals is essential prior to embarking on the main piling works. Here the testing regime may need to be considered in two phases comprising preliminary pile testing before the main piling works and then proof testing of working piles.

The testing strategy for pile testing should address a project-specific set of stated objectives, which should include the following: (1) To minimise risk by investigating any uncertainties about the ground conditions, contractor's experience or new piling techniques (2) To optimise the pile design in terms of size, length and factor of safety to confirm any pile installation criteria such as founding strata identification, pile set or pile refusal criteria (3) To assess buildability, site variability, pile uplift, soil remoulding along the pile shaft or relaxation at the pile toe, (4) To check that the pile performance meets the required load/settlement behaviour during loading (Federation of Piling Specialists, 2006).

This paper is intended to present the study of design validation by comparing the ultimate load of loading test with the its design.

TABLE 1  
FLAW OCCURRENCE RATIO

Location	No.of piles	Testi ng	Piles with		Ref.
			Nu	[	
United Kingdo m	9,550	Soni c (anal og)	161	1.7	1
Californi a	2,986	Most ly radio activ e	-	20	2
US site X	470	Visu al inspe ction	-	64?	2
US site Y	171	Visu al inspe ction	-	76?	2
Asia	300	Visu al	-	>20	2
Italy	6,865	Ultra		12	3
Israel site "R"	253	Soni c (digit al)	57	22.5	4
	40	Ultra sonic	26	65	4
Israel	65	Ultra	28	4	4

1. Fleming et al. (1992)
2. O'Neill & Sarhan (2004)
3. Faiella & Suprebo (1998)
4. Piletest.com files

## 2. Kentledge Test.

Should the ground conditions or site constraints preclude the use of reaction piles, the alternative is to use kentledge. A frame is assembled over the pile to be tested on top of which an amount of weight (a minimum 110 to 120% of maximum test load) is safely stacked. This takes the form of concrete blocks of regular dimensions and weight although steel ingots can be used provided that their weight can be assessed with reasonable accuracy. The size of the testing apparatus is generally a function of the pile size and loading to be applied. At the time of assembly, the presence of the additional cranes and associated transport deliveries will increase this working area.

The test used type of static load testing, that is the Maintained Load Test (MLT). In the MLT, the load is applied to the pile in discrete increments and the resulting pile movement/

settlement monitored. Subsequent load increments are only applied when the minimum specified time period has elapsed and the rates of induced settlement are below the specified criteria. The normal Indonesia practice is to load the pile up to design verification load (DVL), then to unload back to zero loading. Subsequent load cycles are applied, taking the loading to specified values above the DVL depending on the requirements of the test. The test is conducted from January 9, 2012 until January 11, 2012 and determining the load/settlement performance of a pile under working loads up to 2 times design working load conditions.

## 3. Case Study.

### 3.1. Site Geology

The project is located in central of Jakarta. As is generally the ground in Jakarta, the upper layer, consisting of clay that comes from the sea, so it called marine clay. If that soil is tested, it was found that they content high levels of salt. In this project that soil is located at a depth of -0.50 m to a depth of -15.00 m, so thick as 14.5 m. From the drill logs, soil type is dominated by silty clay soil, with a value of N such as 6-10, medium consistency.

Under this layer, there is a lens of sandy soil from -15.00m to a depth -19.00 m. This soil is the result of lava flows from a volcano that erupted thousands years ago. This soil is usually used as the foundation of story building. The soil is hard and dense with a value of N spt = 50. The problem is, there are underground layers of clay / silt that has a value of N spt = 28 to 21, medium to stiff consistency, located at a depth of -19.00 m to -30.00 m, thickness of 11m. This clay type over consolidated (OC).

Under this layer, there is a layer of dense sand, with a value of N = 50. This soil also from the lava of a volcano, located at a depth of -30.00 m to -50.00 m, 20 m thick. So, the tip of pile will lay on this layer. While in the depth of -50 m to -60 m the layer of clay is found.

See Fig. 1 to 3.




Fig. 1 Drilling Log and SPT from 0.00- 20.00m




Fig. 3 Drilling Log and SPT from 40.00- 60.00m




Fig. 2 Drilling Log and SPT from 20.00- 40.00m

### 3.2. Simplified Soil Mechanics Method Design

To calculate the capacity of pile, the Simplified Soil Mechanics method is used. Semi-empirical correlations have been extensively developed relating both shaft resistance and base resistance of bored piles to N-values from Standard Penetration Tests (SPT "N" values). This study uses that correlation for computing bearing capacity of pile.

#### 3.2.1. Ultimate shaft capacity

Undrained Shear Strength ( $S_u$ ), and adhesion factor  $\alpha$  of cohesive soil are computed using empirical correlation of  $N_{spt}$  from Terzaghi dan Peck, (1967), Sowers, (1979) and Kulhawy, (1991). See Fig. 4. and 5




Fig. 4 Relationship between Undrained Shear Strength ( $S_u$ ) and  $N_{spt}$  for cohesive soil (Terzaghi dan Peck, (1967), Sowers, (1979))




Fig. 5 Relationship between Undrained Shear Strength ( $S_u$ ) and Adhesion Factor for cohesive soil (Kulhawey, (1991))




Fig. 6 Relationship between Ultimate Side Resistance and  $N_{spt}$  for cohesionless soil (Wright, (1977))

For non cohesive soil, the ultimate side resistance are computed using Wright, (1977) chart. See Fig. 3.  
 The ultimate shaft capacity is computed using  $Q_{su} = \sum_i f_{su} * P_s$   
 Where :

$f_{su}$  = Unit shaft resistance for each layer of embedded soil  
 $P_s$  = Perimeter of pile.  
 $i$  = Number of soil layers  
 The calculation is shown in table 1.

3.2.2. Ultimate base capacity.

Pile tip is at elevation of -39.00 m, in hard silty sand ,dark gray, medium and very dense cemented. The value  $N_{spt} = 50/0$ , meaning the soil has been hit 50 times, and no decrease. Such soil is found begin -31.00 m , so, the depth is 8 m (10 times the diameter of the pile) on the pile tip. This is ensured that the hard layer can clamp the pile, so that the custody of pile tip can work well. Under the pile tip there is a hard clayey silt ( $N = 50/8$ ) as deep as 1m, followed by silty hard sand ( $N = 50$ ). So the pile tip is supported also by the hard ground. Ultimate side resistance in non-cohesive soil ( $q_p$ ) is calculated by using graphs of Reese & Wright, (1977). See Fig. 7.




Fig. 7 Relationship between Ultimate Base Resistance and  $N_{spt}$  for cohesionless soil (Reese & Wright, (1977))

The ultimate base capacity is computed using  $Q_{bu} = A_p * q_{pu}$   
 Where :  
 $q_{pu}$  = Unit base resistance for the bearing layer of soil.  
 $A_p$  = Area of pile.  
 The calculation is shown in Table II

TABLE II  
 ULTIMATE SHAFT RESISTANCE USING SIMPLIFIED SOIL MECHANICS METHOD

Depth (m)	N spt	Su * (kg/cm2)	Ultimate Shaft Resistance (Qs)							Type of Soil
			Adhesion factor α** (-)	fs		Pile perimeter (m)	q * (ton)	Qs cum ult (ton)		
				(1)	(2)				(3)=(1)*(2)	
Fill Material										
-1	6	0,40	0,87	0,35	3,48	2,51	8,74	8,74		
-2	6	0,40	0,87	0,35	3,48	2,51	8,74	17,48		
-3	7	0,47	0,79	0,37	3,69	2,51	9,26	26,74		
-4	7	0,47	0,79	0,37	3,69	2,51	9,26	36,01		clay
-5	7	0,47	0,79	0,37	3,69	2,51	9,26	45,27		
-6	7	0,47	0,79	0,37	3,69	2,51	9,26	54,53		
-7	8	0,53	0,69	0,37	3,68	2,51	9,24	63,77		
-8	8	0,53	0,69	0,37	3,68	2,51	9,24	73,02		
-9	6	0,40	0,87	0,35	3,48	2,51	8,74	81,76		
-10	6	0,40	0,87	0,35	3,48	2,51	8,74	90,50		
-11	10	0,67	0,59	0,39	3,93	2,51	9,88	100,38		
-12	15	0,50	0,71	0,36	3,55	2,51	8,92	109,30		
-13	23	0,77	0,55	0,42	4,22	2,51	10,59	119,89		clayey silt
-14	37	1,22	0,44	0,54	5,35	2,51	13,45	133,34		ML
-15	50			1,50	15,00	2,51	37,68	171,02		
-16	50			1,50	15,00	2,51	37,68	208,70		silty sand
-17	50			1,50	15,00	2,51	37,68	246,38		SM
-18	44			1,32	13,20	2,51	33,16	279,54		
-19	28			0,84	8,40	2,51	21,10	300,64		
-20	25	0,83	0,53	0,44	4,42	2,51	11,05	311,73		clayey silt,ML
-21	22	1,47	0,4	0,59	5,87	2,51	14,74	326,47		
-22	23	1,53	0,4	0,61	6,13	2,51	15,41	341,87		silty clay
-23	24	1,60	0,39	0,62	6,24	2,51	15,67	357,55		CL
-24	22	1,43	0,41	0,59	5,88	2,51	14,76	372,31		
-25	19			0,57	5,70	2,51	14,32	386,63		silty sand,SM
-26	20	0,67	0,59	0,39	3,93	2,51	9,88	396,51		
-27	21	0,70	0,58	0,41	4,06	2,51	10,20	406,71		clayey silt
-28	19	0,63	0,61	0,39	3,86	2,51	9,70	416,41		ML
-29	17	1,13	0,45	0,51	5,10	2,51	12,81	429,23		silty clay,CL
-30	39			1,16	11,55	2,51	29,01	458,24		
-31	50			1,50	15,00	2,51	37,68	495,92		
-32	50			1,50	15,00	2,51	37,68	533,60		
-33	50			1,50	15,00	2,51	37,68	571,28		silty sand
-34	50			1,50	15,00	2,51	37,68	608,96		SM
-35	50			1,50	15,00	2,51	37,68	646,64		
-36	50			1,50	15,00	2,51	37,68	684,32		
-37	50			1,50	15,00	2,51	37,68	722,00		
-38	50			1,50	15,00	2,51	37,68	759,68		
-39	50			1,50	15,00	2,51	37,68	797,36		

TABLE III.  
 ULTIMATE BASE CAPACITY USING SIMPLIFIED SOIL MECHANICS  
 METHOD

Depth (m)	N spt	Ultimate Base Capacity (Qp)		
		Non cohesive Qp (ton/m2) (1)	Pile Area (m2) (2)	Qp ult (ton) (3)=(1)*(2)
-39	50	365,05	0,50	183,40

### 3.2.3. Ultimate bearing capacity.

So, the ultimate bearing capacity of pile is  $Q_{ult} = Q_s + Q_p = 797,36 + 183,40 = 980$  ton.

The design working load of pile is half of ultimate bearing capacity that is 400 ton.

### 3.3. Kentledge Pile Loading Test.

#### 3.3.1.Date of test.

The pile loading test performed by the system Kentledge D 1143-81 section 5.2. Pile is casted on October 18, 2011 and the test on 9 to 11 of January, 2012. So, between the casting and the test, there is time of 82 days. So the age of the concrete has reached more than 28 days. Predicted compressive strength is above 42 MPa, so that is strong enough to be burdened.

Within 82 days,it expected that the soil damaged caused by drilling and casting has been improved and the water table has returned to its original position. So that the loading test results did not change with time and has a long-term results.See Fig. 8.

#### 3.3.2. Loading

The maximum consecutive loading are 200 tonnes (50%), 400 tons (100%), 600 tons (150%) and 800 tons (200% of design working load).In this test, the pile is loaded and unloaded in unequal increments.The load is maintained under each increment until the rate of settlement is acceptably small. At two times the design load, the load is maintained for 12 hours. After the required holding time, the loading is added in increment of 50%, 33%-25%, 50%-17%, 50%-13% with 1 hour between increments, in maximum load of 200 ton, 400 ton, 600 ton and 800 ton. As well as reducing load during unloading. The greater the maximum load, the smaller the load change. This is done to save time without sacrificing testing accuracy. Relationship between load and settlement can be seen in Table IV. and Fig 9.

TABLE IV  
 RELATIONSHIP BETWEEN LOAD AND SETTLEMENT IN MAXIMUM  
 LOAD OF 200 TON, 400 TON, AND 800 TON (LOADING AND  
 UNLOADING)

Design Working Load 400 ton							
Max 200 ton (50%)		Max 400 ton (100%)		Max 600 ton (150%)		Max 800 ton (200%)	
Load (ton)	Settlement (mm)	Load (ton)	Settlement (mm)	Load (ton)	Settlement (mm)	Load (ton)	Settlement (mm)
0	0,000	0	0,01	0	1,46	0	3,49
100	0,510	200	1,56	200	3,07	200	5,18
200	1,300	300	3,09	400	5,28	400	7,55
100	0,980	400	4,87	500	7,30	600	10,73
0	0,010	300	4,26	600	10,12	700	14,36
		200	3,75	500	9,84	800	21,78
		0	1,46	400	9,25	800	24,48
				200	7,01	600	23,85
				0	3,49	400	21,54
						200	18,79
						0	14,04




Fig. 8. Kentledge test

Davisson MT method produces  $Q_{ult} = 730$  tons. The calculation of the value of  $x$  can be seen in Table IV. Graph both methods are shown in Fig. 10. and Fig. 11.




Fig. 10 Ultimate bearing capacity ( $Q_{ult}$ ) of bored pile using Mazurkiewicz method




Fig. 11 Ultimate bearing capacity ( $Q_{ult}$ ) of bored pile using Davisson MT method




Fig. 9 Relationship between load and settlement in maximum load of 200 ton, 400 ton, 600 ton and 800 ton (loading and unloading)

### 3.3.3. Calculation of ultimate bearing capacity Kentledge Pile Loading Test.

Calculation of bearing capacity using two methods, namely Mazurkiewicz and Davisson MT methods. Mazurkiewicz method produce the ultimate bearing capacity  $Q_{ult} = 850$  tons and

TABEL 4

COMPUTATION OF X VALUE IN DAVISSON MT METHOD.

D (cm)	D (inch)	D/120 (inch)	$X = 0,15 + \frac{D}{120}$ (inch)	$X = 0,15 + \frac{D}{120}$ (mm)
80	31,496	0,262	0,412	10,477

## 4. Analysis and Conclusion.

### 4.1. Loading unloading with a maximum load of 200 tons.

The magnitude of decrease and increase of settlement in the loading test, it can be seen in Table III.

On the maximum load of 200 tons, the settlement that occurs when the maximum load of 200 tons, that is 1.30 mm is recovered when the load is reduced, so the pile return on the initial conditions. The settlement of last unloading is 0.01 mm = 0 mm. That's because the base resistance of the pile has not yet happened. So all of the burden borne by the pile (which retracts and extends back) and shaft resistance.

At first, pile fell by 1.30 mm, it cause the workings of friction between the soil and pile. Once the load is reduced, the shaft friction "raise" the pile back, so the magnitude of setting

is 0 mm. Thus it can be said that based on this test, the shaft resistance that happened at that time is 200 tonnes. The shaft resistance of pile happens if there is a movement of 0.5% to 1% pile diameter, while the base resistance occurs if there is a movement of 10% to 20% pile diameter. Pile diameter is 80 cm, shaft resistance of pile occurs if there is a movement of 4 mm to 8 mm, while the base resistance occurs if there is a movement of 8 cm to 16 cm.

4.2. Loading unloading with a maximum load of over 200 tons.

In the next load those are 400 tons, 600 tons and 800 tons, it is likely custody ends work. Settlement of the pile did not recover. The amount of setting occurred at 1.45 mm, 2.03 mm and 10.55 mm. While the recovered settlement of pile is equal to 3.41 mm, 6.63 mm and 10.44 mm. At burdened loading - unloading, there was recover setting and unrecover setting. Recover setting can be said elastic deformation and unrecover setting is said plastic deformation. It turned out that an increase in the percentage ratio of plastic deformation to the elastic deformation increases very sharply when the load approached its ultimate. Of development, it can be concluded that the pile near the ultimate carrying capacity at the time weighed 800 tons (200% design working load). See Table V and Fig. 12




Fig. 12 The development of plastic deformation

TABLE V.  
ELASTIC AND PLASTIC DEFORMATION DURING LOADING TEST.

No	Max Loa (ton)	Settlement		Plastic Elastic deformati on (%)	
		Unrecover (Plastic deformatio n)	Recover (Elastic deformatio n)		
		(mm)	(mm)		
1	200	1,3	0,01	1,29	0,8%
2	400	4,87	1,45	3,41	42,5%
3	600	10,1	2,03	6,63	30,6%

4	800	24,4	8	10,55	10,44	101,1%
---	-----	------	---	-------	-------	--------

4.3. . The difference of ultimate bearing capacity between Kentledge loading test and Simplified Soil Mechanics method.

Calculation of bearing capacity of pile based on loading test is analysed using two methods, those are Mazurkiewicz and Davisson MT methods. Mazurkiewicz method produce the ultimate bearing capacity Q ult = 850 tons and Davisson MT method produces Q ult = 730 tons. While the calculations using the Simplified Soil Mechanics method using SPT data produces the ultimate bearing capacity = 998 tons. See Table VI. The difference between Kentledge loading test and Simplified Soil Mechanics method are 13 % and 25%, if the ultimate capacity of Kentledge loading test is computed using Mazurkiewicz and Davisson MT method.

TABEL VI  
COMPARATION AMONG ULTIMATE BEARING CAPACITY OF PILE USING SIMPLIFIED SOIL MECHANICS METHOD , MAZURKIEWICZ DAN DAVISSON MT METHOD.

No	Method	Q ultimate (ton)
1	Simplified Soil Mechanics method & SPT	980
2	Mazurkiewicz	850
3	Davisson MT	730

ACKNOWLEDGEMENT:

The Author wish to thanks to Mr Prof. Paulus.P.Raharjo, Ph.D and Mr Eddy Triyanto Sujatmiko for their enthusiastic support.

REFERENCES:

- [1] Amir, J.M. (2002): Single-Tube Ultrasonic Testing of Pile Integrity, ASCE Deep Foundation Congress, Vol 1 pp.836-850, Orland.
- [2] Amir, J.M. (2007): Discussion on "Reliability Evaluation of Cross-Hole Sonic Logging for Bored Pile Integrity" by D.Q. Li, L. M. Zhang, W. H. Tang, J Geotech Div ASCE, Vol 133 No. 3, pp. 342-34.
- [3] Davisson, M.T. (1970): Static measurement of pile behaviour, Design and instalation of cellular structures, Envvo Publishing Co, edited by H-Y Fang, pp 159-164.
- [4] Faiella, D and Suprebo, S. (1998): Integrity not-destructive tests of deep foundations by means of sonic methods – analysis of the results collected on 37 sites in Italy, Proc.Seminar on deep foundations on bored and augered piles, Ghent, pp. 209-213
- [5] Fleming, W.G.K., Weltman, A.J., Randolph, M.F. and Elson, W.K (1992): Piling Engineering, 2nd ed., Blackie, Glasgow, pp. 280-281
- [6] Handbook on Pile Load Testing, (2006), Federation of Piling Specialists, Beckenham, Kent, BR3 1NR
- [7] Kulhawy, F.H. (1983): Transmission Line Structure Foundation for uplift Compression Loading, Reseach Report EL-2870, Electric Power Research Institute (EPRI), California.
- [8] O'Neill, M.W. and Sarhan, H.A. (2004): Structural resistance factors for drilled shafts considering construction flaws, Conf. Deep Foundations ASCE, Los Angeles, pp. 166-185
- [9] Reese, L.C., Wright, S.J. (1977): Drill Shaft Design and Construction Manual, Vol 1, US Department of Transportation, Washington, D.C.



Hosted By :  
Faculty of Engineering and Faculty of Computer Science  
Universitas Bandar Lampung (UBL)

