

Infrastructure Health Monitoring System (SHM) Development, a Necessity for Maintenance and Investigation

¹Priyo Suprobo

¹Faimun

²Arie Febry

¹ Institute Technology of Sepuluh Nopember, FTSP, Surabaya

² Phd Student of Institute Technology of Sepuluh Nopember, FTSP, Surabaya

Abstract-*Failure of Kutai Bridge already give Indonesia civil engineer a blow in face. The failure which bring cause human accident make a new challenge to Indonesia civil engineer not to wait till failure but to safe before the construction failure. By the development in sensor and monitoring technology the idea become more realistic. Structure Healthy Monitoring (SHM) become new idea to detect, to monitor and to find out the reliability of structure. The development and research in Indonesia for SHM till now are presented and compared to other country. SHM research are need to predict behaviour of bridge by using data from monitoring to gain healthy condition.*

Keywords- *Monitoring, Bridge, Structural Healthy Monitoring (SHM)*

Preface

Engineer of civil engineering are risk takers, this means design and build any construction are related with human life. Any mistake to design and build will create a disaster. History already record an engineer fault in civil engineering that involve to human accident.

Civil engineering are different than another engineering. Other could create a prototype to see it behaviour and create a standard to avoid mistake. But in civil engineering every construction are different, have their own characteristic and have their own strenght. Many factor create this condition from paper to field problem when that construction build until mother nature involve.

Even in Melchers (1987) say that civil engineering failure that created a problem are smallest than other human activity (0.1 millions / years) depending to smoke activities risk which is 1000 millions / years. But still when a construction fail many people will watch and investigate more that dead by smoke. A civil construction failure happens in many ways. First a bad design by civil enginner consultant, a bad construction by civil contractor which create a bad composition of material strenght or detailing to building which is very poor.

And last a deterioration of construction to nature or envirotment.

If construction are human being, we can consider the condition of it life are related to all this above. This might be a health condition for it. The different to human being are it does not grow by itself but it have a deterioration which alway say as life time of construction.

Failure of construction before the life time will create a shock effect for all, specially for all civil engineer. lets just say our tragedy of Kutai Kartanegara Bridge. Failure of Kutai Bridge bring many things to Indonesia engineers. Investigation, history and strenght of bridge are learn and calculate. Cause of the failure are considered and take by note so there will be no other tragedy like it. This tragedy created a change in civil engineer to create and seek the more ways to convince the other or next bridge will be safe for no more tragedy.

Beside of making better design and build effort, this will also bring a consideration about how to see a healthy condition of structure. Question like how healthy actually this construction or actually how much old this construction (which mean to life time design) and how much strenght remain in construction are

ask. If question above are need to find out the reliability of construction.

Reliability of construction which mean to it healthy are new part of civil engineering know as Structural Healthy Monitoring (SHM). This part idea are monitoring construction behaviour from it build to deterioration of it. So by learning all data and condition related to construction, question above can be answer and can be use to predict maintance and deterioration to construction. By ideas to safe and not to wait till failure, the changes of civil engineer idea may be different in next period

From all construction, brigde might be a start for SHM, this consideration come because bridge have a unique condition compare to other construction. Bridge are use every day by human but inspection are not often because not like building, people use bridge but not related to fell it condition compare to building. Bridge are use every day by different load type, different composition of load and dynamic load occur in it. Other than that bridge are skeleton construction type, which mean SHM can be use directly to it main construction.

This idea to change from how to detect, to monitor and to safe the structure with SHM come with development of technology. Century ago or at least fifty year ago, this idea to monitor might be not accross in civil engineer mind. Technology of sensor and computer monitoring become a fast growing in electro engineering nowadays, by combining it to our basic concept structure behaviour, the idea from wait till to monitor might become a solution for life safety. This condition mean a challenge for all of civil engineer to be ready to this change specially for Indonesia engineer to use the monitoring system to the idea to safe before the construction fail.

This paper aim to detail Indonesia SHM application depending to other countries, progress of SHM in bridge and next research for SHM which can be

challenge to all of us to the next future of construction.

SHM Development in Other Country

Research for SHM are now main idea in several countries, because the patern of research are large and need integration of them. Figure 1 show main idea of SHM research.




Figure 1 : Part of SHM Research (Srinivasan,2011).

According to data, research for SHM started from 1996 as define in table 1.

Table 1. SHM Research in other country

Country	Year Start
Hungaria	2003
Swiss	1998
Prancis	2000
Cina	1998
Jerman	1996
Austria	1999
Amerika	1998
Thailand	2001
Singapura	1997

Source : Helmut, 2009

Research for SHM from other country consist from laboratory and field test using many sensor and many method to define result of sensor. And there is

still no agreement reach about standard for SHM data read.

Oth (2012) from Luxenburg has propose a method for deflection of bridge from their field experiment using vibration data. Meanwhile Zhu (2012) from USA, propose a frequency to create a mode shape in FEM for the bridge. Another research come from Resnik (2012) in Jerman which propose to use natural frequency as base standard of healthy.

Other type research of monitoring might come from other type than vibration data, Yukio (2005) propose to use a robot detection method for monitoring and vehicle detection robot system just like in figure 2.




Figure 2 : Vehicle Robot Sensor (Yukio, 2005)

Meanwhile Korea system for monitoring are called with SBBMS propose for deflection and temperature sensor to determine condition of bridge (Koh,2005).

Research for SHM until 2012 are still trying to propose their method so it can be use as standard of healthy bridge. Korea research are now harvest data from their major bridge which is Sohae bridge using sensor as figure 3 and 4.




Figure 3 : Sensor in Sohae bridge




Figure 4 : Sohae bridge harvest data

Indonesia SHM Development

Indonesia started SHM development by integrated SHM system in Suramadu bridge. Around 514 sensors are attached consist of vibration, corrotion, global positioning system, temperature and wind sensor. Suramadu sensor are using cable to transfer data.

But the main idea getting a SHM attached not only to harvest data but also to read data from it. Which mean not only apparatus but human resource must be applied for SHM data. Research about SHM can be started when Suramadu Bridge SHM start their harvesting data, but with Kutai bridge failure need for human resource and cheap apparatus become more significant to do. Indonesia which is create by Island with a lot of river which mean there are a lot of small, medium and long bridge need to monitor.

A Research for Indonesia SHM

Need for Indonesia SHM research are cheap, can be transfer to control unit with long range, moveabel apparatus and can be define a bridge healthy in control monitor system. This need refer to envirotment condition and resource of indonesia.

Because of this need SHM study group referring a condition of wireless sensor using GSM packet data to sent. Meanwhile from civil engineer need a algorithm for analysis data sent from wireless in second to define bridge healthy




Figure 5 : Indonesia SHM Model System

SHM study group define a vibration data harvest from accelerometer can be a start for define bridge behaviour. Test will be do in laboratory scale using bridge model and full scale test in field using wireless sensor apparatus which is still in prototype .




Figure 6 : Laboratory scale bridge test
And test trust of bridge already started, as define in figure 5.




Figure 7 : Truss scale test

Test in field harvest vibration data around 48 hours. This data are sort to create a type of define data to use. Filtering and whitening data using Fast ICA method.

TABLE 2. VEHICLE DATA
COMPARRISON

No	Vehicle Type	Load	Speed km/ hours
1a	Truck With Wood As Load	Full	26
1b	Truck With Wood As Load	Full	20
2a	Concrete Mix Truck	Empty	24
2b	Concrete Mix Truck	Full	24
3a	Fuel Tank 10000	Full	29
3b	Fuel Tank 10000 litre 3 in row	Full	29

Comparison using raw data are show above




Figure 8. Case 1 in raw vibration data




Figure 9. Data Result FastICA no 1b, 1b




Figure 10. Case 2 in raw vibration data




Figure 11. Data Result FastICA no 2b




Figure 12. Case 2 in Raw Vibration Data




Figure 13a Data Result FastICA no 3a




Figure 13b Data Result FastICA no 3b

This comparison above show that vibration in bridge monitoring system need a database of load to create a standard frequency for define condition of bridge healthy. And test must be do in real time to get a prediction for bridge healthy. Research of wireless sensor and wireless system to bridge monitoring system are need to gain more information about bridge behaviour.

Acknowledgements

This is Part of ITS Laboratory Based Education (LBE) in Structural Health Monitoring (SHM) Research funded by JICA Predict Phase 2 – Japan And National Higher Education Directorate General of Indonesia

- Reference**
- [1] E. Mohammed and A. Sreenivas, "Infrastructure Health in Civil Engineering, Theory and Components, CRC Press, 2012
 - [2] Koh, recent development of bridge Health monitoring system in Korea , in Farhad A book "sensing issue in Civil Engineering SHM, 2005, Springer, USA
 - [3] Melchers R. E, structural Reliability and Analysis Prediction, Ellis Horwood Ltd, UK, 1987
 - [4] O. Adrien and P Matteo, "Structural Health Monitoring Using Wireless Technologies : An Ambient Vibration Test on the Adolphe Bridge, Luxembourg City, Hindawi Publishing Corporation advances in Civil Engineering Volume 2012, 2012
 - [5] Resnik, Implementation and analysis of vibration measurements obtained from monitoring the Magdeburg water Bridge, 2013, German
 - [6] Yukio, Monitoring technology for maintance and management of urban highways in Japan, in Farhad A book "sensing issue in Civil Engineering SHM, 2005, Springer, USA

Zhu, Vibration testing of a steel girder using cable and wireless sensor, 2012 , USA