ISSN: 2301-6590





Proceedings ICETD 2012

The First International Conference in Engineering and Technology Development



Universitas Bandar Lampung 20 - 21, June 2012 Lampung, Indonesia The First International Conference on Engineering and Technology Development (ICETD 2012) Faculty of Engineering and Faculty of Computer Science, Universitat Bandar Lampung

PREFACE

The activities of the International Conference is in line and very appropriate with the vision and mission of the UBL to promote training and education as well as research in these areas.

On behave of the First International Conference of Engineering and Technology Development (ICETD 2012) organizing committee; we are very pleased with the very good responses especially from the keynote speakers and from the participants. It is noteworthy to point out that about 45 technical papers were received for this conference

The participants of conference come from many well known universities, among others: Universitas Bandar Lampung, International Islamic University Malaysia, University Malaysia Trengganu, Nanyang Technological University, Curtin University of Technology Australia, University Putra Malaysia, Jamal Mohamed College India, ITB, Mercu Buana University, National University Malaysia, Surya Institute Jakarta, Diponogoro University, Unila, Universitas Malahayati, University Pelita Harapan, STIMIK Kristen Newmann, BPPT Lampung, Nurtanio University Bandung, STIMIK Tarakanita, University Sultan Ageng Tirtayasa, and Pelita Bangsa.

I would like to express my deepest gratitude to the International Advisory Board members, sponsors and also welcome to all keynote speakers and all participants. I am also grateful to all organizing committee and all of the reviewers which contribute to the high standard of the conference. Also I would like to express my deepest gratitude to the Rector which give us endless support to these activities, such that the conference can be administrated on time.

Bandar Lampung, 20 Juni 2012

Mustofa Usman, Ph.D ICETD Chairman The First International Conference on Engineering and Technology Development (ICETD 2012) Faculty of Engineering and Faculty of Computer Science, Universitas Bandar Languag

1SSN 2301-0

PROCEEDINGS The First International Conference in Engineering and Technology Development (ICETD 2012) UNIVERSITAS BANDAR LAMPUNG Bandar Lampung,Indonesia June, 20-21 2012

Sterring Commite Chairman Mustofa Usman

> Co-Chairman Marzuki

Technical Committee Ahmad Cucus Agus Sukoco Dina Ika Wahyuningsih

Treasure Maria Shusanti Febrianti

Committee Member Indyah Kumoro Fritz Akhmad Nuzir Baginda Simaimban Berry Salatar Harpain Yuthsi Aprilinda Usman Rizal Andala Rama P.Barusman Yanuar Dwi Prasetyo

International Advisory Board

Ahmad F. Ismail, Malaysia Hon Wei Leong, Singapore Mustofa Usman, Indonesia Imad Khamis, USA Moses L. Singih, Indonesia Y. M.Barusman, Indonesia Andreas Dress, Germany Rozlan Alias, Malaysia Faiz A.M.Elfaki, Malaysia Rudi Irawan, Indonesia Warsono, Indonesia Gusri Ibrahim, Indonesia Raihan Othman, Malaysia Jamal I Daoud, Malaysia Zeng Bing Zen, China Riza Muhida, Indonesia Tjin Swee Chuan, Singapor Heri Riyanto, Indonesia Khomsahrial R, Indonesia Agus Wahyudi, Indonesia Rony Purba, Indonesia Lilies Widojoko, Indonesia Alex Tribuana S, Indonesia First International Conference on Engineering and Technology Development (ICETD 2012) willy of Engineering and Faculty of Computer Science, Universitas Bandar Lampung

ISSN 2301-6590

Organizing Committee

Chair Person Prof. DR. Khomsahrial Romli, M.Si

Vice Chair Person Drs. Harpain, M.A.T., M.M

Secretary Fritz Akhmad Nuzir, S.T., M.A Ahmad Cucus, S.Kom., M.Kom

> Treasure Dian Agustina, S.E

Special Events

DR. Zulfi Diane Zaini, SH., MH DR. Baginda Simaibang, M.Ed Zainab Ompu Jainah, SH., MH DR. Alex Tribuana S., ST., MM Erlangga, S.Kom

Recepcionist

Berry Salatar, A.Md Yanuar Dwi Prasetyo, S.Pd.I., M.A Siti Rahma Wati, S.E Ardiansyah, ST., MT Sofie Islamia Ishar, S.T., M.T Taqwan Thamrin, S.T., M.Sc

Transportation and Acomodation

Irawati, SE Usman Rizal, S.T., MMSi Hendri Dunan, S.E., M.M Rifandi Ritonga, S.H Desi Puspita Sari, S.E Roby Yuli Endra, S.Kom Tanto Lailam, S.H Ilyas Sadad, S.T., M.T

Publication and Documentation

Ir. Indriati Agustina Gultom, M.M Monica Mutiara Tinambunan, S.I.Kom., M.I.Kom Noning Verawati, S.Sos Hesti, S.H Rifandi Ritonga, SH The First International Conference on Engineering and Technology Development (ICETD 2012) Faculty of Engineering and Faculty of Computer Science, Universitas Bandar Lampung

ISSN 2301-6

Olivia Tjioener, S.E., M.M Violita, S.I.Kom

Cosumption Dra. Yulfriwini, M.T Dra. Agustuti Handayani, M.M Susilowati, ST., MT Wiwin Susanty, S.Kom Reni Nursyanti, S.Kom DR.Dra. Ida Farida, M.Si

Facility and Decoration Zainal Abidin, SE Ahyar Saleh, SE Eko Suhardiyanto Dina Ika Wahyuningsih, A.Md Wagino Sugimin

Table Of Content

0	zing Committeei
Table	Of Contentv
Kevno	te Speaker
1.	Zinc-Air Battery – Powering Electric Vehicles to Smart Active Labels
	Dr. Raihan Othman
2.	Enhancing Heat Transper Using Nanofluids(abstract)
	Prof. Ahmad Faris Ismail
3.	Rapid Prototyping and Evaluation for Green Manufacturing
	RizaMuhida, Ph.D
4.	Indonesia's Challenge to Combat Climate Change Using Clean Energy
	Rudi Irawan, Ph.D
5.	Paraboloid-Ellipsoid Programming Problem
	Prof.Dr. Ismail Bin Mohd
6.	Model Development of Children Under Mortality Rate With Group Method of Data
	Handling Dr. IingLukman
7.	The Modified CW1 Algorithm For The Degree Restricted Minimum Spanning Tree Problem
	Wamiliana, Ph.D
8.	The Fibre Optic Sensor in Biomedical Engineering and Biophotonics
0.	Prof. TjinSweeChuan
a 1	
Speak 1.	er Web-Based Service Optimization with JSON-RPC Platform in Java and PHP
1.	Web-Based Service Optimization with JSON-KPC Platorin in Java and PTIP WachyuHari Haji
2.	Trouble Ticketing System Based Standard ISO10002: 2004 To Improve Handling of
	Complaints Responsibility
	Ahmad Cucus, Marzuki, AgusSukoco, Maria ShusantiFebrianti, Huda Budi Pamungkas
3.	Design of Warehouse Management Application Tool for Controlling The Supply Chain

Anita Ratnasari, Edi Kartawijaya10

5. Implementing CBR on The College Rankings Based on Webometrics with EPSBED's Data and Webometrics Knowledge

(ICETD Universi	5 6 6 6 1	ISSN 2301-6590
Tucuny	Marzuki , Maria Shusanti F, Ahmad Cucus , AgusSukoco	
6.	Paypal Analysis as e-Payment in The e-Business Development Nomi Br Sinulingga	
7.	Decision Support System for Determination of Employees Using Fuzzy Decision Tre Sinawaty#1, YusniAmaliah	
8.	Analysis of Factors Influencing Consumer Behavior Bring Their Own Shopping Bag (Case Study KecamatanTembalang) Aries Susanty, DyahIkaRinawati, FairuzZakiah	
9.	The Use of Edge Coloring Concept for Solving The Time Schedule Problem at Senio High School (Case Study at SMAN 9 Bandarlampung) RahmanIndraKesuma, Wamiliana, MachudorYusman	
10.	Analysis Of Web-Education Based on ISO / IEC 9126-4 For The Measurement Of Q Of Use Marzuki, AgusSukoco, Ahmad Cucus, Maria ShusantiFebrianti, Lisa Devilia	
11.	The Used of Video Tracking for Developing a Simple Virtual Boxing David HabsaraHareva, Martin	
12.	M-Government as Solutions for E-Government problems in Indonesia Ahmad Cucus, Marzuki, AgusSukoco, Maria ShusantiFebrianti	
13.	Open Source ERP for SME Tristiyanto	
14.	Improvement in Performance of WLAN 802.11e Using Genetic Fuzzy Admission C SetiyoBudiyanto	
15.	Cloud Computing: Current and Future TaqwanThamrin, Marzuki, Reni Nursyanti, Andala Rama Putra	75
16.	Implementing Information Technology, Information System And Its Application In Making The Blue Print for The One Stop Permission Services Sri AgustinaRumapea,HumuntalRumapea	
17.	Integration System Of Web Based And SMS Gateway For Information System Of T Study EndykNoviyantono, Aidil	
18.	Fuzzy Logic Applied To Intelligent Traffic Light EndykNoviyantono, Muhammad	
19.	Solving and Modeling Ken-ken Puzzleby Using Hybrid Genetics Algorithm Olivia Johanna, Samuel Lukas, Kie Van IvankySaputra	
20.	GIS Habitat Based Models Spatial Analysis to Determine The Suitability Of Habitat Elephants AgusSukoco	

21.	The Course Management System Workflow-Oriented to Control Admission and Academic Process Usman Rizal, YuthsiAprilinda
22.	Fuzzy Graphs With Equal Fuzzy Domination And Independent Domination Numbers A.Nagoorgani, P. Vijayalakshmi
23.	Solving Pixel Puzzle Using Rule-Based Techniques and Best First Search Dina Stefani, Arnold Aribowo, Kie Van IvankySaputra, Samuel Lukas
24.	Capacity Needs for Public Safety Communication Use 700 MHz as Common Frequencyin Greater Jakarta Area SetiyoBudiyanto
25.	Impact of Implementation Information Technology on Accounting Sarjito Surya
26.	Document Management System Based on Paperless WiwinSusanty, TaqwanThamrin, Erlangga, Ahmad Cucus
27.	Traceability Part For Meter A14C5 In PT Mecoindo Of The Measurement Of Quality Of Use Suratman, WahyuHadiKristanto, AsepSuprianto, MuhamadFatchan, DendyPramudito
28.	Designing and Planning Tourism Park with Environment and Quality Vision and Information Technology-Based(Case Study: Natural Tourism Park Raman Dam) Fritz A. Nuzir, AgusSukoco, Alex T
29.	Smart House Development Based On Microcontroller AVR-ATMEGA328 Haryansyah, Fitriansyah Ahmad, Hadriansa
30.	Analyze The Characteristic of Rainfall and Intensity Duration Frequency (IDF) Curve at Lampung Province Susilowati
31.	The Research of Four Sugarcane Variety (Saccharum officinarum) as The Raw Materials of Bioethanol Production in Negara Bumi Ilir Lampung M.C.Tri Atmodjo, Agus Eko T, Sigit Setiadi, Nurul Rusdi, Ngatinem JP, Rina, Melina, Agus Himawan
32.	Design an Inverter for Residential Wind Generator Riza Muhida, Afzeri Tamsir, Rudi Irawan, Ahmad Firdaus A. Zaidi
33.	The Research of Two Sugarcane Variety (<i>Saccharum officinarum</i>) as The Raw Materials of Bioethanol Production in Negara Bumi Ilir - Lampung M.C. Tri Atmodjo, Agus Eko T., Sigit Setiadi, Nurul Rusdi, Ngatinem JP, Rina, Melina, Agus H.
34.	Design of Plate Cutting Machine For Cane Cutter (Saccharum Oficinarum) Use Asetilin Gas M,C, Tri Atmodjo , Tumpal O.R , Sigit D.Puspito

(ICETD Universi	national Conference on Engineering and Technology Development 2012) tas Bandar Lampung od Engineering and Faculty of Computer Science	ISSN 2301-6590
35.	Behaviour of Sandwiched Concrete Beam under Flexural Loading Firdaus, Rosidawani	
36.	Diesel Particulate Matter Distribution of DI Diesel Engine Using Tire Disposal Fuel Agung Sudrajad	
37.	Microstructure Alterations of Ti-6Al-4V ELI during Turning by Using Tungsten Car Inserts under Dry Cutting Condition Ibrahim, G.A. Arinal, H, Zulhanif, Haron, C.H.C	
38.	Validation Study of Simplified Soil Mechanics Method Design with Kentledge Pile Loading Test of Bored Pile Lilies Widojoko	
39.	Performance Assessment Tool for Transportation Infrastructure and Urban Developm for Tourism Diana Lisa	
40.	Earthquake Resistant House Building Structure Ardiansyah	

Solving and Modeling Ken-ken Puzzle byUsingHybridGeneticsAlgorithm

Olivia Johanna^{#1}, Samuel Lukas^{#2}, Kie Van Ivanky Saputra^{#2}

^{#1}Department of Technique Information, ^{#2}Mathematics, PelitaHarapan University UPH Tower, LippoKarawaci, Tangerang, 15811, Indonesia

¹Dark_g4lzz@yahoo.com ²Samuel.lukas@uph.edu ³Ivanky82@gmail.com

Abstract— Kenken is logic puzzle which similar to Sudoku. The basic rules are same as Sudoku. As in sudoku, the goal of each puzzle is to fill a grid with digits 1 through 4 for a 4×4 grid, 1 through 5 for a 5×5, etc. No digit appears more than once in any row or column. Grids range in size from 3×3 to 9×9. Unlike sudoku, KenKen grids are divided into heavily outlined groups of cells often called "cages" and the numbers in the cells of each cage must produce a certain "target" number when combined using a specified mathematical operation (addition, subtraction, multiplication or division).). For example, a three-cell cage specifying addition and a target number of 6 in a 4×4 puzzle might be satisfied with the digits 1, 2, and 3. Digits may be repeated within a cage, as long as they are not in the same row or column. No operation is relevant for a single-cell cage: placing the "target" in the cell is the only possibility. The target number and operation appear in the upper left-hand corner of the cage. Initially, none of the cell in a cage in Kenken has value. Kenken is such a simple logic *puzzle*, but finding the solution is quite complex, especially for harder problem. Therefore, research is conducted to develop software which can solve Kenken problem.

The research will produce software that can solve kenken puzzle byusingheuristic search and hybrid genetic algorithm. Heuristic search will be done by applying certain logic rules. If the puzzle is still not being able to be solved then hybrid genetic algorithm will be run. How can the software solve the kenken problem will be explained in this paper.

After conducting some researchs and implementing the software and doing the testing, some experiments were conducted and it proved that the hybrid genetics algorithm can solve the kenken puzzle and bbased on experiment result, the size of *puzzle* and the difficulty of problems affect the time needed to find a solution


Keywords-Kenken logic puzzle, heuristics, genetics algorithm

I. INTRODUCTION

As a kind of arithmetic and grid puzzle, Kenken is also recognized as KenDoku, Calcudoku atau Mathdoku. It was invented in 2004 by the Japanese math teacher Tetsuya Miyamoto. The name derives from the Japanese word for cleverness.

As in sudoku, the goal of each puzzle is to fill a grid with digits *I* through *n* for a $n \times n$ grid, so that no digit appears more than once in any row or column. Grids range in size from 3×3 to 9×9 . Additionally, KenKen grids are divided into heavily outlined groups of cells often called "cages" and the numbers

in the cells of each cage must produce a certain "target" number when combined using a specified mathematical operation (either addition, subtraction, multiplication or division). If the operation is subtraction or division then the cage has to consist of two cells. The target number and operation appear in the upper left-hand corner of the cage.Figure 1 is an example of Kenken6x6.





There are no many papers discussing on how to solve Kenken puzzle. However, some logical rules can be applied. There are Singlesquare, naked pair, nakedtriple, eviltwin, Hidden single, Killer combination, and X-wing.

Through this paper will be discussed on how to implement the rules so that computer can solve the problems being generated by Will Shortz in Kenken Pro 2 game.

II. HEURISTICS SEARCH AND GENETIC ALGORITHM

Heuristic search is an AI search technique that employs heuristic for its moves. *Heuristic* is a rule of thumb that probably leads to a solution. Heuristics play a major role in search strategies because of exponential nature of the most problems. Heuristics help to reduce the number of alternatives from an exponential number to a polynomial number. In a general sense, the term heuristic is used for any advice that is often effective, but is not guaranteed to work in every case. 1st International Conference on Engineering and Technology Development (**ICETD 2012**) Universitas Bandar Lampung Faculty of Engineering and Faculty of Computer Science

There are some heuristics search techniques: Generate and Test, Hill Climbing, and Best First Search. This paper discusses generate and test through genetic algorithm.

A. Rules based system in Kenken

Some logic rules are also used in solving Kenken puzzle. They are Single square, nakedpair, nakedtriple, eviltwin, Hidden single, Killer combination, and X-wing. Single square rule is applied if a cage has only one cell. It means the value of that cell is same as a target number.

Naked pair rule is used if there are two cells in a row or in a column that have precisely the same two possible values to fill the cells. It means other cells in that row or column respectively has no chance to have the same possible value with that of that the two cells have. Figure 2 represents on how this naked pair rule works. The cells marked with green precisely have two possible values (1 or 7). These are a naked pair. Since 1 and 7 must occur in these two cells, we can eliminate 1 and 7 from the cells marked with red.



Figure 2. An example on how to detect Naked pair Rule


Naked triple works identical with naked pair but the number of cell is three instead of two. It implies the number of possible values to fill the cells is also three.

Evil twin is the easiest rule. If a cage consists f two cells and whenever one cell is solved then the other cell is easy - it is simply the value is needed to make the sum work out. For example from Figure 3, once cell in the bottom left corner is solved with the- 4, then the square above it is 9. In fact, the rule can be generalized for larger areas. The last unsolved cell in an area is simply the value needed to make the sum work out.



Figure 3.An example of Evil Twin Rule.

Hidden singles are a simple enough concept, but are often quite hard to spot. The definition of a hidden single is when a cell is the only one of its possible value in an entire row, column. From figure 4, the possible values to solve the most left cell are 3, 5 or 7. However this row must have a "7" in it somewhere. It can be seen that only that cell that has a "7" as one of its candidates. That is hidden single. That cell should be solved with "7".




Killer combination is the most crucial rule. This rule is possibly applied if the cells covered in a cage areallin one row or column and the mathematical operation is addition. There is a unique possible numbers for cells for this killer combination related with the cage size. For example, a clue of target value is 3 in a cage of size 2 can only have 1 or 2 in it. It means possible number from 3 to 9 can be removed from those cells. If a cage with target number is 23 then the only possible number for the cells are 6, 8, or 9. This killer combination for cage size 2 and for any cage value is tabulated in Table 1. The table can be expanded to the other cage size.

TABLE 1.KILLER COMBINATION FOR CAGE SIZE 2

Cage size	Cage value	Combination
2	3	1/2
2	4	1/3
2	17	8/9
2	16	7/9

X-wing rule stated that when there are only two possible cells for a value in each two different rows and these candidates lie also in the same columns, then all other candidates for this value in the columns can be eliminated. Figure 5 shows an example of this rule.



If A turns out to be a 7 then it rules out a 7 at C as well as B. Because A andCD are 'locked' then D must be a 7. So a 7 MUST be present at A, D or B, C. If this is the case then any other 7's along the edge of our rectangle are redundant. We can remove the 7's marked in the green squares.

B. Genetic algorithm

Genetic algorithms (GA) is a kind of generate and test heuristics techniques. It was inspired by the behaviour of natural systems; the terminology used to describe them is a mix from both biological and computer fields. A genetic algorithm manipulates strings of information, usually called chromosomes. These encode potential solutions to a given problem. Chromosomes are evaluated and assigned a score (fitness value) in terms of how well they solve the given problem according to criteria defined by the programmer. These fitness values are used as a probability of survival during a round of reproduction. New chromosomes are produced by combining two (or more) parent chromosomes. 1st International Conference on Engineering and Technology Development (ICETD 2012) Universitas Bandar Lampung

Faculty od Engineering and Faculty of Computer Science

This process is designed to lead to a succession of fitter offspring, each encoding better solutions, until an acceptably good solution is found.

The working principle of a GA is illustrated below. The major steps involved are the generation of a population of solutions, finding the objective function and fitness function and the application of genetic operators. These aspects are described briefly in the subsection below.

Formulate initial population Randomly initialize population Repeat Evaluate objective function Apply genetic operators Reproduction Crossover Mutation Until stopping criteria

III. MODELLING OF KENKEN PUZZLE

Ken-ken puzzle of size $n \ge n$ has n^2 cells. Cell located in row, b and column, k is labelled as $C_{b,k} = bn + k$ and the value of that cell is $V(C_{b,k}) \in \{1,2,...,n\}$. Aith-cagelabelled A_i is a set of cells, $A_i = \{C_{b,k}\}$. It correlates with one arithmetic operator $o_i \in \{+,-,x,\div\}$ and one target number $H_i \in N$. This is the three rules in making the Ken-ken problem $|A_i| = 1 \rightarrow O_i = \phi$, $O_i \in \{-,\div\} \rightarrow |A_i| = 2$ and $\forall C_{b,k} \rightarrow C_{b,k} \in \exists! A_i$. The purpose of the puzzle is to find the value $V(C_{b,k})$ and meet the constrains :

$$\begin{split} 1 & |A_i| = 1 \land C_{b,k} \in A_i \to V(C_{b,k}) = H_i \\ 2 & O_i \in \{-, \div\} \land A_i = \{C_{a,b}, C_{p,q}\} \to |V(C_{a,b}) - V(C_{p,q})| = H_i \\ 3 & O_i \in \{\div\} \land A_i = \{C_{a,b}, C_{p,q}\} \to V(C_{a,b}) / V(C_{p,q}) = H_i \\ 4 & O_i \in \{+\} \to \sum_{C_{b,k} \in A_i} V(C_{b,k}) = H_i \\ 5 & O_i \in \{x\} \to \prod_{C_{b,k} \in A_i} V(C_{b,k}) = H_i \end{split}$$

The flow chart of solving Ken-ken puzzle is represented in figure 6.




Figure 6. Flow chart of Solving Kenken Puzzle

Rule based search is started by assuming all unknown value of cells by all possible values to fill that cell without breaking the constraints, $P(C_{b,k}) = \{1, 2, ..., n\}$. after the value of one cell has been determined, the possible values of a certain cells respectively were updated. For example using

naked single rule is stated as equation 1, will cause all possible values for all cells in a row and in a columnis updated stated in equation 2 and 3. Applying naked pair is stated in equation 4 for row and 5 for column. Other rules are also defined.

$$|P(C_{b,k})| = 1 \land x \in P(C_{b,k}) \to V(C_{b,k}) = x$$

$$\tag{1}$$


$$(V(C_{b,k}) = x) \land (\forall a \in \{1, 2, ..., n\}) \to P(C_{a,k}) = P(C_{a,k}) - \{x\}$$
(2)

$$(V(C_{b,k}) = x) \land (\forall q \in \{1, 2, ..., n\}) \to P(C_{b,q}) = P(C_{b,q}) - \{x\}$$
(3)

$$|P(C_{b,k1})| = |P(C_{b,k2})| = 2 \land P(C_{b,k1}) = P(C_{b,k2}) \to P(C_{b,q}) = P(C_{b,q}) - P(C_{b,k1})$$
(4)

$$|P(C_{bl,k})| = |P(C_{b2,k})| = 2 \land P(C_{bl,k}) = P(C_{b2,k}) \to P(C_{p,k}) = P(C_{p,k}) - P(C_{bl,k})$$
(5)

Hybrid genetic algorithm is used while the puzzle still is not able be solved after exercising all the rules repetitively. It started by encoding the chromosome. One chromosome consists of k number of segments, $m \le n$.One segment is a set of genes that of unsolved cells in that segment.



A Segment represents a row or a column. Segments are ordered in a chromosome. An example of one chromosome from Kenken puzzle in Figure 7 is 34 35 | 28 29 2425 | 0 4 5 1 2 3 | 11 6 9 7 8 10| 12 14 15 17 16 13 | 20 18 1923 21 22.

Figure 7. An example of Kenken puzzle 6x6

Objective function will be calculated after the generation value of gene on chromosome has been done. Value for gene *j*-th on a chromosome was represented by w_j . w_j isset 0 if gen is not solved, otherwise is set 1. For a chromosome with number of genes *k*, fitness function is shown by the equation below.

$$x_{j} = \begin{cases} 0 & , w_{j} = 0 \\ 1 & , w_{j} \neq 0 \end{cases} \qquad fitness = \frac{\sum_{j=0}^{k} x_{j}}{k} \tag{6}$$

Consequently, the solution of the puzzle is to find out the chromosome with the fitness value is 1.

In reproduction process, crossover, two chromosomes, parents, will be crossed to produce another two chromosomes, children, with N-segments crossover methodology. This process is shown in Figure 8.





1st International Conference on Engineering and Technology Development (**ICETD 2012**) Universitas Bandar Lampung

Faculty of Engineering and Faculty of Computer Science

Exchange mutation is used to get another possible chromosome. Mutation is done between genes in the same segment. Figure 9 is an example of a mutation process between two genes on the same segment.

IV. EXPERIMENT RESULTS

Two types of experiments were conducted. They are to know how fast the system can solve the puzzle accordance to the size and the level of the difficulty of the puzzle. Size variations of Kenken puzzle were experimented 5×5 , 7×7 and 9×9 with variation of level of difficulty easy, medium, hard and expert. For each category, 10 sample puzzles are used. Some of the puzzle can be solved only by rule based where as the other should be with hybrid genetics algorithm. Table 2 showed the percentage of puzzle that can be solved only by using rule base search.

TABLE 2. PERCENTAGE OF PROBLEMS THAT CAN BE SOLVED USING BUILE BASE SEARCH

ROLE BASE SEARCH					
Size	Level of difficulty				
Size	Easy	Medium	Hard	Expert	
5×5	100%	80%	50%	0%	
7×7	100%	60%	0%	0%	
9 × 9	100%	90%	0%	0%	

Average time (in millisecond) of 10 attempts for a certain puzzleper unit cell can be seen in Table 3.

TABLE 3. AVERAGE TIME TO EACH CELL IN MILLISECOND

~.	C Level of difficulty				
Siz	Nu		Mediu		
e	m	Easy	m	Hard	Expert
	1	1.480 0	0.5600	1.2000	17.4400
	2	0.480 0	0.4800	0.5200	33.1600
	3	0.480 0	0.4800	0.5600	1.1200
	4	0.480 0	0.5200	0.5200	4.1600
5x5	5	0.480 0	0.5200	0.5200	1.4800
	6	0.640 0	0.4800	0.9600	1.0800
	7	0.480 0	1.2000	1.7600	0.9600
	8	0.480 0	0.8000	0.7200	1.2400
	9	0.600	0.4800	2.6800	1.4400

		0			
	10	0.440 0	0.4800	0.9600	3.0400
	1	0.693 9	24.979 6	3.1694	1.2429
	2	0.755 1	2.3673	1.8143	7.0673
	3	0.693 9	0.9796	4.9755	3.0163
	4	0.673 5	2.6327	2.4347	1.5918
77	5	0.673 5	0.7143	2.0041	1.7449
7x7	6	0.775 5	0.6939	5.6959	1.0184
	7	0.734 7	0.7347	9.3796	2.5531
	8	0.734 7	0.7959	119.770 4	1.8878
	9	0.734 7	0.6735	8.2673	1.3592
	10	0.673 5	0.6735	1.0082	96.3367
	1	1.086 4	0.9753	31.5099	7.3457
	2	0.864 2	0.9877	160.019 8	113.654 3
	3	0.975 3	1.2716	0.7568	0.9457
	4	1.148 1	1.8025	23.8963	24.1086
9x9	5	0.827 2	0.9259	5.3914	285.714 8
787	6	0.876 5	1.2963	0.8346	0.9840
	7	1.197 5	1.3951	0.7049	374.771 6
	8	0.839 5	1.0000	3.5605	1.6210
	9	0.888 9	1.1605	0.9272	28.4617
	10	0.901 2	0.9877	1.2630	37.7383

Analyzing the data with F-test, it proved that completion time was independent with puzzle size for any level difficulty. F calculation for level difficulty easy, medium, hard and expert is 2.2, 0.3, 0.3 and 0.8 where as F table is 4.74. It means that for any type of level difficulty, the average time to solve each cell is independence with the size of the puzzle. Further investigation showed that there is no significant different on average elapse time to solve each cell between level difficulty easy and medium however there was between easy and expert. It was caused by most of easy and medium problems could be solved only by using rule based search. On the other hand, all expert problems used hybrid genetic 1st International Conference on Engineering and Technology Development (ICETD 2012)
 Universitas Bandar Lampung
 Faculty of Engineering and Faculty of Computer Science

algorithm. Interestingly, there was no significant different elapse time between level difficulty hard and expert.

V. CONCLUSIONS

Through these experiments, hybrid genetic algorithm system can solve kenken puzzle successfully. Kenken puzzle level of difficulty expert can not be done only by using single square, naked pair, naked triple, evil twin, hidden single, killer combination, and X-wing rules. It needs to applies others sophisticated logic rules.

REFERENCES

- [1] Kenken, Puzzles That Make You Smarter. [Online] Available: <u>http://www.kenken.com/</u>
- [2] Davis, Tom. Kenken for Teachers, 2010.
- [3] Lukas, S., Arnold A., Junaidi., "Aplication of Hybrid Genetic Algorithm for solving Sudoku Puzzle", Proc Mathematics National Conference, Manado., Indonesia, 2010, p 339-346
- [4] Andries P. Engelbrecht, Computational intelligence : An Introduction Second Edition, Part III p.125-p.283, John Wiley & Sons Ltd, The Atrium, Southern Gate, Chichester, West Sussex PO19 8SQ, England, 2007.

Hosted By : Faculty of Engineering and Faculty of Computer Science Universitas Bandar Lampung (UBL)

